

1. Purpose

To outline acceptable variations to the deemed-to-comply provisions of the Residential Design Codes (R-Codes) for medium-density single houses in development areas, and to identify methods for implementation, to ensure consistent application across Western Australia.

2. Background

R-MD Codes

Residential densities have increased in recent years in response to a number of factors including the implementation of the key policy initiatives of Directions 2031, market demand for smaller lots, and efforts to improve housing affordability. In some cases, development on smaller lots using the standard R-Codes has resulted in built form outcomes that do not fit comfortably on the subject lot or relate well to the existing streetscape.

The ability to vary deemed-to-comply requirements is prescribed in Part 7 of the R-Codes. Variations to the deemed-to-comply requirements outlined in clause 7.3.1 do not require WAPC approval, however, variations to any other deemed-to-comply requirements are subject to WAPC approval.

A number of different planning instruments can be used to vary the R-Codes, including local planning scheme provisions, local development plans, and local planning policies. The different instruments apply the variations to different scales of development, from select sites to entire residential estates. Over time, the introduction of variations to the R-Codes via these different planning instruments has increased, and as a result there are now many variations to the R-Codes that apply in different local government areas across the State.

The WAPC's operational design policy, *Liveable Neighbourhoods*, recommends the use of limited local development plans for 'constrained' sites where it needs to be demonstrated that a single house can be constructed on the proposed lot and meet the performance requirements of the R-Codes.

In order to achieve this, local development plans may be used to vary the deemed-to-comply requirements of the R-Codes in order to facilitate development.

Over time, however, their use for this purpose has extended such that some local development plans now apply R-Code variations across entire development areas rather than being used for specific constrained sites as intended. In other cases, local development plans substantially amend some deemed-to-comply requirements (e.g. open space – minimum total percentage of site) to facilitate the development of large dwellings on small lots.

In order to respond to this increased use of R-Codes variations, a working group of key government, development and building industry stakeholders was formed to discuss the resulting issues and to identify potential solutions.

3. Medium-density single house development standards (R-MD Codes)

The medium-density single house development standards (R-MD Codes) at **Appendix 1** are based on contemporary housing typologies and incorporate existing R-Codes variations that have been applied to date in approved planning instruments.

The R-MD Codes can be used as a variation to existing deemed-to-comply requirements for building and garage setbacks (clauses 5.1.2, 5.1.3

and 5.2.1), open space (clause 5.1.4), parking (clause 5.3.3), visual privacy (clause 5.4.1) and solar access (clause 5.4.2).

All other relevant R-Codes standards will continue to apply.

Lot width for double garages

The R-MD Codes establish a minimum 10.5 metre lot width for single houses with double garages, where sole access is from a primary street.

This increase in minimum lot width will not be applied retrospectively and does not apply to subdivision applications lodged or approved prior to 8 May 2015. Where an approved structure plan or local development plan has a 10 metre lot for a single house with double garage, this approved plan will be used by the WAPC or the local government to determine the subdivision or development application.

4. Implementation

R-MD Codes

The R-MD Codes can be adopted as a local planning policy that varies the deemed-to-comply requirements of the R-Codes, and can be applied in development zones.

Under the *Planning and Development (Local Planning Schemes) Regulations 2015* (the Regulations), the deemed-to-comply requirements of the R-Codes can be varied via a scheme amendment, local planning policy, activity centre plan or local development plan.

As such, implementation of the R-MD Codes can be either through incorporation into a local planning scheme via a scheme amendment, or by the adoption of a local planning policy.

Under Schedule 2, Part 7, Clause 61(4)(c) of the deemed provisions of the Regulations, the deemed-to-comply requirements of the R-Codes can be amended or replaced by local planning policy. Any development outlined in 61(1)(c) and (d) that is in accordance with a local planning policy adopted under this provision (and which also achieves compliance with all other R-Code provisions), is exempt from the requirement to obtain development approval.

Implementation of the R-MD Codes via local planning policies will allow local development plans to again be used for their intended purpose, of facilitating development on smaller constrained sites.

The R-MD Codes are contained in **Appendix 1**. A model local planning policy to adopt the R-MD Codes is contained in **Appendix 2**.

The WAPC will not generally support further variations to the provisions outlined at **Appendix 1**. However, variations that provide for innovative housing typologies (not considered in the specified typical lot size / type) and that deliver positive community outcomes may be considered at the WAPC's discretion.

The WAPC has resolved in accordance with Schedule 2, Part 2, Clause 4(1) of the Regulations that adoption of the R-MD Codes (as contained in **Appendix 1**) as a local planning policy does not require public advertising.

Upon adoption of such a local planning policy, the local government must notify the WAPC of the resolution. The WAPC will then confirm that the policy is in accordance with this planning bulletin.

5. Review and future R-Codes amendment

The WAPC will monitor the implementation of the R-MD Codes following implementation, and will conduct reviews at six monthly intervals with a view to ultimate inclusion in the R-Codes.

6. Further information

Enquiries or correspondence on this planning bulletin should be sent by email to rcodesreview@planning.wa.gov.au or by post to:

Planning Manager, Urban Policy
Policy and Priority Initiatives
Department for Planning
Gordon Stephenson House
140 William Street
Perth, WA, 6000

Please quote reference
DP/15/00045/1

Information relevant to this
Planning Bulletin is published at
www.planning.wa.gov.au

Appendix 1

Single house standards for medium density housing in development zones (R-MD Codes)

R-Code	Lot type and size	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
		R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
R-MD – R60	Rear load 5m x 30m – 150m ² 6m x 30m – 180m ² Front load 8.5m x 20m – 170m ² 7.5m x 25m – 187.5m ²	2m minimum, no average 1m to porch / veranda no maximum length 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, max 3.5m high and 3m average height 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	40% open space (60% site cover) 16m ² courtyard 1/3 required outdoor living area (OLA) may be covered Minimum dimension 4m	An outdoor living area (OLA) with an area of 10% of the lot size or 20m ² , whichever is greater, directly accessible from a habitable room of the dwelling and located behind the street setback area At least 70% of the OLA must be uncovered and includes areas under eaves which adjoin uncovered areas The OLA has a minimum 3m length or width dimension No other R-Codes site cover standards apply	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements Garage width limited to maximum 50% of lot frontage where garage in front of or within 1m of building	Rear load 0.5m garage setback to laneway Front load 4.5m garage setback from the primary street and 1.5m from a secondary street The garage setback from the primary street may be reduced to 4m where an existing or planned footpath or shared path is located more than 0.5m from the street boundary For front loaded lots with street frontages between 10.5 and 12m, a double garage is permitted to a maximum width of 6m as viewed from the street subject to: - Garage setback a minimum of 0.5m behind the building alignment - A major opening to a habitable room directly facing the primary street - An entry feature consisting of a porch or veranda with a minimum depth of 1.2m; and - No vehicular crossover wider than 4.5m where it meets the street Lots with a frontage less than 10.5m or not compliant with above require single or tandem garaging	Two on-site bays	One on-site bay where dwelling has two bedrooms or less	50% of the adjoining site area	No maximum overshadowing	3m to bedrooms and studies 4.5m to all other major openings 6m to balconies or similar	No privacy provisions apply		
R-MD – R40	Rear load 7.5m x 30m – 225m ² Front load 8.5m x 30m – 255m ² 8.5m x 25m – 212.5m ² 10 x 20m – 200m ² 10 x 25m – 250m ² 12.5m x 20m – 250m ²	4m 1.5m to porch / veranda no maximum length 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings) Boundary walls 2/3 length one side boundary, maximum 3.5m high and 3m average height 1m minimum to secondary street Front fences within the primary street setback area being a maximum height of 900mm above natural ground level, measured from the primary street side of the front fence	45% open space (55% site cover) 20m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements	As per R-MD – R60	Two on-site bays	As per R-Codes	35% of the adjoining site area	No maximum overshadowing for wall height 3.5m or less No maximum overshadowing for wall height greater than 3.5m where overshadowing is confined to the front half of the lot, if overshadowing intrudes into rear half of the lot, shadow cast does not exceed 35%	4.5m to bedrooms and studies 6m to all other major openings 7.5m to balconies or similar No maximum overshadowing for wall height greater than 3.5m where overshadowing is confined to the front half of the lot, if overshadowing intrudes into rear half of the lot, shadow cast does not exceed 35%	R-Codes clause 5.4.1 C1.1 applies, however the setback distances are 3m to bedrooms and studies, 4.5m to major openings to habitable rooms other than bedrooms and studies and 6m to unenclosed outdoor active habitable spaces		

Appendix 1

Single house standards for medium density housing in development zones (R-MD Codes)

R-Code	Lot type and size	Street setback and front fences		Lot boundary setback		Open space		Garage setback and width and vehicular access		Parking		Overshadowing		Privacy	
		R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision	R-Codes	R-MD provision
R-MD – R30	Rear load 10m x 30m – 300m ²	4m	2m minimum, no average	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings)	Boundary setbacks As per R-MD – R60	45% open space (55% site cover)	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide	As per R-MD – R60	Two on-site bays	As per R-Codes	35% of the adjoining site area	As per R-MD – R40	4.5m to bedrooms and studies	As per R-MD – R40
	Front load 10m x 30m – 300m ² 15m x 20m – 300m ²		1.5m to porch / veranda no maximum length	Boundary walls to both side boundaries subject to: 2/3 length to one side boundary, 1/3 max length to second side boundary for 3.5m high and 3m average height	Boundary walls As per R-MD – R60	24m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m		Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements					6m to all other major openings	7.5m to balconies or similar	
R-MD – 25	Front load 12.5m x 25m – 312.5m ²	6m	3m	Boundary setbacks 1 to 1.5m for wall height 3.5m and less (subject to wall length and major openings)	Boundary setbacks As per R-MD – R60	50% open space (50% site cover)	As per R-MD – R60	Rear load Nil – provided laneway is minimum of 6m wide	As per R-MD – R60	Two on-site bays	As per R-Codes	25% of the adjoining site area	As per R-MD – R40, however if overshadowing intrudes into rear half of the lot, shadow cast does not exceed 25%	4.5m to bedrooms and studies	As per R-MD – R40
	15m x 25m – 375m ² 12.5m x 30m – 375m ²		1.5m to porch / veranda no maximum length 1.5m minimum to secondary street	Boundary walls 2/3 length one side boundary, max 3.5m high and 3m average height to one side boundary	Boundary walls As per R-MD – R30	30m ² courtyard 1/3 required OLA area may be covered Minimum dimension 4m		Front load 4.5m or 0.5m behind dwelling alignment subject to averaging requirements					6m to all other major openings	7.5m to balconies or similar	

Appendix 2

Model Local Planning Policy

Variation to deemed-to-comply requirements of the R-Codes - Medium-density single house development standards (R-MD Codes)

Purpose

To replace the deemed-to-comply requirements of following clauses of the Residential Design Codes with those set out in the provisions of this policy:

Building and garage setbacks – clauses 5.12, 5.13 and 5.21
Open space – clause 5.1.4
Parking – clause 5.3.3
Visual privacy – clause 5.4.1
Solar access – clause 5.4.2

Definitions / abbreviations

Approved Structure Plan	A structure plan or activity centre plan that has been approved by the WAPC under Part 4 or Part 5 of the City / Town / Shire of Local Planning Scheme No...
Front load	Lots where the primary vehicle access is via the front of the lot and the garage / carport is located at the front of the dwelling
Medium density	R25–R60 density codes
Rear load	Lots where the primary vehicle access is via the rear of the lot, from a street or right of way (ROW) and the garage / carport is located at the back of the dwelling
R-MD / R-MD Codes	Single house standards for medium density housing

Statutory provisions

Development approval will not be required for a single dwelling that complies with the provisions of this policy (and all other deemed-to-comply requirements of the R-Codes), in accordance with clause 61(4)(c) of the deemed provisions of the Scheme.

Application

This policy will apply:

1. in the following structure planning areas: (Insert details of structure plan areas / names); or
2. where the approved structure plan identifies that the R-MD Codes local planning policy applies.

Policy provisions

(Insert the Single House Standards for Medium-density Housing from Appendix 1 of Planning Bulletin 112/2015)

Disclaimer

This document has been published by the Western Australian Planning Commission. Any representation, statement, opinion or advice expressed or implied in this publication is made in good faith and on the basis that the government, its employees and agents are not liable for any damage or loss whatsoever which may occur as a result of action taken or not taken, as the case may be, in respect of any representation, statement, opinion or advice referred to herein. Professional advice should be obtained before applying the information contained in this document to particular circumstances.

© Western Australia Planning Commission

Published by the
Western Australian Planning Commission
Gordon Stephenson House
140 William Street
Perth WA 6000

Locked Bag 2506
Perth WA 6001

Published April 2016

ISSN 1324-9142

website: www.planning.wa.gov.au
email: corporate@planning.wa.gov.au

tel: 08 6551 9000
fax: 08 6551 9001
National Relay Service: 13 36 77
infoline: 1800 626 477

This document is available
in alternative formats on
application to Department of
Planning Communication Services



GOVERNMENT OF
WESTERN AUSTRALIA